

# CoveStix 4400

PREMIUM LIGHTWEIGHT COVE BASE ADHESIVE



## LIGHTWEIGHT RUBBER & VINYL COVE BASE • DESIGNED FOR DIFFICULT TO BOND COVE BASE

CoveStix 4400 is lighter and easier to handle and spread than conventional heavy cove base adhesives. A 4 gallon pail of CoveStix 4400 weighs approximately 28 lbs compared to other cove base adhesives that can weigh over 40lbs. CoveStix 4400 is recommended for installing difficult to bond vinyl (PVC), rubber and specialty cove base on clean, dry interior walls. CoveStix 4400 has the high grab and wet strength to keep corners tight and to hold cove base firmly to the wall until it dries. The fast-setting formula provides a durable impact-resistant bond.

### Advantages:

- Lightweight formula-as much as 30% less weight
- Compatible with all common manufactured brands of cove base
- Non-staining, light colored
- SCAQMD Rule 1168 - compliant
- FloorScore® Certified
- Low odor, Low VOC
- Freeze thaw protected to 15° F

### Application:

1. Spread the adhesive using a 1/8" x 1/8" V-Notch trowel or using a 3-hole tube applicator tip.
2. The adhesive may be spread on the wall surface, or on the back of the wall base.
3. Immediately place the wall base into position while the adhesive is freshly applied.
4. Roll the entire strip of base with a small roller in the direction of the previously placed strip.
5. Wipe smudges and clean spills quickly before the adhesive dries. Use a clean cloth dampened with water. Clean tools with water while the adhesive is still wet.
6. Dried adhesive may require the use of a solvent (odorless mineral spirits).

**NOTE:** Follow all cove base manufacturer's instructions regarding trowel size, coverage and application methods.

**CAUTION:** Make certain the surface is porous by cutting away or perforating non-absorbent wall coverings. Do not apply to vinyl wallpaper. XL Brands cannot be responsible for shrinkage caused by unstable cove base.

Coverage on 4" cove (10.16 cm cove):

1/8" x 1/8" V-Notch = 220-240 linear feet per gallon

3 hole applicator tip = 55-60 linear feet per 30 ounce cartridge

Open Time:

20-30 minutes

Shelf Life:

2 years from manufacturing date in an unopened container

Approved Wall Surfaces:

Plaster, brick, wood, concrete, gypsum drywall, plywood

LEED PROGRAM CERTIFICATIONS (where applicable)

- IEQ Credit 4.1—Low Emitting Materials
- IEQ Credit 4.3—Low VOC ratings help qualify installations for this credit as part of a flooring system.
- MR Credit 5—Regional Materials—on jobsites within 500 miles from manufacturing location: Dalton, GA 30721.

TECHNICAL RAPID RESPONSE:

1-706-508-5907 Mon-Fri 8am -5pm EST

24-Hour Emergency in the USA: Chemtrec 1-800-424-9300

**Disclaimer:** Users should determine the suitability of this information or product for their own particular purpose or application. Manufacturer is not responsible for the misuse of this product.

This Technical Data sheet and the information conveyed herein supersede all previous versions.

XL Brands® is a registered trademark of XL Brands, LLC